

**SCHOTTKY BARRIER RECTIFIERS**

REVERSE VOLTAGE - 40 to 60 Volts  
FORWARD CURRENT - 10 Amperes


**FEATURES**

- Metal of silicon rectifier, majority carrier conduction
- Guard ring for transient protection
- Low power loss, high efficiency
- High current capability, low VF
- High surge capacity
- Plastic package has UL flammability classification 94V-0
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

**MECHANICAL DATA**

- Case : TO-220AB molded plastic
- Terminals: Lead Free Plating (Matte Tin Finish)
- Polarity : As marked on the body
- Weight : 0.08 ounces, 2.24 grams
- Mounting position : Any
- Max. mounting torque = 0.5 N.m (5.1 Kgf.cm)

**TO-220AB**



TO-220AB		
DIM.	MIN.	MAX.
A	14.40	15.20
B	9.65	10.67
C	2.54	3.43
D	5.84	6.86
E	8.26	9.28
F	-	4.20
G	12.70	14.73
H	2.29	2.79
I	0.51	1.14
J	0.30	0.64
K	3.53 $\varnothing$	4.09 $\varnothing$
L	3.56	4.83
M	1.14	1.40
N	2.03	2.92
O	1.14	1.70

All Dimensions in millimeter

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

CHARACTERISTICS	SYMBOL	SBL1040CTW	SBL1045CTW	SBL1060CTW	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	40	45	60	V
Maximum RMS Voltage	VRMS	28	31.5	42	V
Maximum DC Blocking Voltage	VDC	40	45	60	V
Maximum Average Forward Rectified Current (See Fig.1) @Tc=95°C	I(AV)	10			A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	IFSM	125			A
Maximum Forward Voltage at 5A DC (Note 1)	VF	0.55		0.7	V
Maximum DC Reverse Current at Rated DC Blocking Voltage @Tj=25°C @Tj=100°C	IR	0.2 5		0.3 40	mA
Typical Junction Capacitance per element (Note 2)	CJ	250			pF
Typical Thermal Resistance (Note 3)	RθJC	3.0			°C/W
Operating Temperature Range	TJ	-55 to +125			°C
Storage Temperature Range	TSTG	-55 to +150			°C

NOTES : 1. 300us Pulse Width, 2% Duty Cycle.  
2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.  
3. Thermal Resistance Junction to Case.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL JUNCTION CAPACITANCE



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.